



Minispot ML 50

Specification sheet



De GLG Minispot ML 50 The features a 50W LED with high intensity and efficiency. It produces very high light output similar to a 90W spot, (3300 Lux on 10 meters) through a specific 20° optic system. The PAN/TILT integrates in fast and quiet movement. It offers a full complement of professional characteristics, including a rotating gobo wheel,

a color wheel, a 3-facet prism, motorized linear focus, 0-100% linear LED dimmer and an variable speed shutter.



Technical Specifications

- 1 * 50 watt white Led Engine 7500K
- 8/16 bit resolution PAN/TILT
- 360° /540°/630° PAN en 90°/ 180° /270° TILT
- 20° beam
- High quality optic system
- 1 rotating gobowheel 6 interchangeable gobos + open
- 1 Colorwheel with 7 colors + open
- Variabel rainbow effect with variable speed
- Automatic focus
- 3-facet prism variable speed adjustment
- Electronic high resolution dimmer
- 25T/sec high speed SHUTTER/strobe effect with variable speed
- LED display
- 11/13 DMX channels USITT DMX-512
- Powercon in
- 3-pin XLR in & out
- Silent fans
- Omega bracket with M8 bolts
- Power:55W
- Dimensions:149(D)*270(B)*366(H)mm
- Weight: 6,6 Kg